



TECHNICAL SHEET

16-535



G-TEK® POLYKOR™ BLENDED GLOVE WITH POLYURETHANE COATED GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips for great abrasion resistance, excellent puncture resistance and outstanding wet/dry grip
- Knit wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing
- Washable, resistant to chemicals, water, and ultraviolet light
- Thumb / Index reinforcement for better wear resistance

APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C)



TECHNICAL DATA

MATERIAL	PolyKor™ Fiber / Polyurethane					
CONSTRUCTION	Seamless knit					
COLOR	Shell: ■ Salt & Pepper / Coating: ■ Gray					
SIZES	6 - 11					
PACKAGING	Single polybag, pack of 12, case of 72					
CASE	30cm x 32cm x 26cm					
CASE WEIGHT	6	7	8	9	10	11
	3.9 kg	4.3 Kg	4.8 Kg	4.9 Kg	5.4 Kg	5.5 Kg
COO	China					

DIMENSIONS (IN/CM)


	6	7	8	9	10	11
A	9.0 / 22.5	9.3 / 23.5	9.6 / 24.5	10 / 25.5	10.4 / 26.5	10.8 / 27.5
B	3.7 / 9.3	3.9 / 9.8	4.1 / 10.3	4.2 / 10.6	4.3 / 10.8	4.3 / 11
H	■ Purple	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

PERFORMANCE PROPERTIES

EN388: 4X43C

ASTM F2992-15 ANSI Cut Level A3 (Adopted by ANSI/ISEA 02/16)

ABRASION	0	1	2	3	4	-
CUT (2003)	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (ISO 13997)	A	B	C	D	E	F



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

PIP FRANCE SAS | 120 Grande Rue | 85570 L'Hermenault | Tel: +33 2 51 50 19 80 | info@pipeurope.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.