



# TECHNICAL SHEET

## 16-854



### G-TEK® POLYKOR™ BLENDED GLOVE WITH NITRILE FOAM COATED GRIP 18 GAUGE

- Seamless construction offers increased comfort and breathability
- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Nitrile is a synthetic rubber compound that offers excellent puncture, tear and abrasion resistance
- Nitrile foam coatings cell structure is designed to channel fluids away from the surface of the object helping improve grip in slightly oily/wet conditions - secure grip in dry conditions
- Knit wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing
- Washable, resistant to chemicals, water, and ultraviolet light
- DMF free
- Thumb reinforcement

#### APPLICATIONS

- Parts assembly
- Material handling
- Equipment maintenance & repair
- Parts cleaning
- Fastening and anchoring

#### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low maximum temperature 140°F (60°C).



#### TECHNICAL DATA

MATERIAL	PolyKor™ Fiber / Nitrile Coating					
CONSTRUCTION	18 Gauge Seamless Knit					
COLOR	Shell: ■ Salt&Pepper / Coating: ■ Black					
WRIST STYLE	Knit Wrist					
SIZES	6 - 11					
PACKAGING	1 pair per bag, 12 pairs per dozen, 6 dozen per case					
CASE DIMENSIONS	38cm x 30cm x 28cm					
CASE WEIGHT	6	7	8	9	10	11
	3.2 kgs	3.4 kgs	3.6 kgs	3.8 kgs	4.0 kgs	4.2 kgs
COO	China					

#### PERFORMANCE PROPERTIES

EN388: 4X42D						
ABRASION	0	1	2	3	4	-
CUT (2003)	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (ISO 13997)	A	B	C	D	E	F

#### DIMENSIONS (IN/CM)

	6	7	8	9	10	11
A	8.4 / 21.5	8.8 / 22.5	9.25 / 23.5	9.6 / 24.5	10.2 / 26	10.6 / 27
B	3.5 / 9	3.6 / 9.3	3.9 / 10	4.1 / 10.5	4.3 / 11	4.4 / 11.3
H	■ Violet	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

